

2020 Valley Speedway
Hobby Stock
(Enduro) Rules
Dirt Demons

This class is designed for the entry-level driver.

This is a class to learn in and most importantly to have fun.

Safety is our first priority. Your car will not be allowed to race if deemed unsafe by Technical Director.

1. Any American or Foreign 4 or 6 cylinder passenger car or truck. No four wheel drive or all wheel drive. No Turbochargers or Superchargers. No four wheel steer cars.
2. Springs, shocks and struts must remain stock.
3. Any wheel and tire size allowed with dot tires must fit in 7 inch wide gauge.
4. **Must have muffler.** Exhaust must exit from under and outside of car.
5. Must remove all flammable material except dash (may run sheet metal dash).
6. Must remove all glass. Windshield must be removed. Remove all exterior trim, molding, headlights, taillights, lens covers, etc. Trunk lid and front hood latches must be removed and ~~replaced with hood pins~~.
7. A six-point roll cage is mandatory. Cage must be welded to 2" by 2" square tubing that is welded to the rocker panels and the floor. Roll cage tubing must be minimum of 1 1/2" by .095 highly recommended 1 3/4" by .095. A minimum of three door bars is required on driver's side. Earnhardt bar must be installed.
8. Racing seats and belts required and must be mounted to roll cage. NOT to the floor. Must be the same specification as general rules except belts can be a maximum of four years old. However they must be in excellent condition without frays, tears, etc. Tech Director has final say on belts.
9. All cars must have a master on/off switch located in center of dash and labeled. This master switch **must** disconnect the battery and fuel pump.
10. All cars must have an operable racing window net.
11. Stock fuel tank allowed if located in front of rear axle. If not located in front of rear axle, must be replaced with a fuel cell and to be approved by Technical Director.
12. Battery may be moved inside of driver's compartment. Battery must be securely mounted to floor in a battery box with 2 metal straps min. 1" wide.
13. **Car may have welded spider gears (not recommended)**
14. Fire extinguisher must be mounted in reach of driver.
15. Air bag must be disconnected.
16. A snell approved racing helmet required.
17. Fire retardant racing suit, and gloves are required.
18. Cars must be painted and lettered neatly. A minimum of 18" numbers on both doors. Roof numbers must be facing fan side.
19. Car number and driver need to register at Valley Speedway.
20. **Car must weigh a minimum of 2,100 lbs for 4 cylinder and 2,400 lbs for 6 cylinder cars at the end of the race with driver in car.**